

Amendments to the Claims

Please cancel claims 11 and 44-46.

Please amend claims 1, 4, 5, 9, 10, 12, 19-23, 53, and 58 as shown below.

Listing of Claims

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently amended) A method for routing calls in a telecommunication system, the method comprising:
 - detecting data for a call from a calling party to a called party;
 - determining if the called party is a subscriber to a call routing service, including
 - receiving the call at a switch of the telecommunication system,
 - extracting call routing information for the call,
 - communicating a query including a directory number for the called party
 - from the switch to a service control point of the telecommunication
 - system,
 - in response to the query, retrieving information related to the directory
 - number, including an associated service subscription, from a
 - database of the service control point;
 - if the called party is not a subscriber to the call routing service, processing the call
 - normally; and
 - routing the call in accordance with information about the calling party and the called party.
2. (Original) The method of claim 1 further comprising:
 - providing a call routing message to the calling party customized for the calling party based at least in part on the information about the calling party.
3. (Original) The method of claim 1 further comprising:

providing a menu of call routing options to the calling party customized for the calling party based at least in part on the information about the calling party.

4. (Currently amended) The method of claim 1 further comprising:
~~determining if the called party is a subscriber to a call routing service;~~
retrieving a subscriber profile for the subscriber; and
providing a call routing message to the calling party customized for the calling party based on the information about the calling party and the subscriber profile.
5. (Currently amended) The method of claim 1 further comprising:
~~determining if the called party is a subscriber to a call routing service;~~
retrieving a subscriber profile for the subscriber; and
providing a menu of call routing options to the calling party customized for the calling party based on the information about the calling party and subscriber profile.
6. (Original) The method of claim 1 further comprising:
determining calling line identification information for the calling party; and
providing a menu of call routing options to the calling party customized for the calling party based at least in part on the calling line identification information.
7. (Original) The method of claim 6 further comprising:
retrieving a stored subscriber profile associated with the called party;
identifying possible call routing options; and
providing a menu of call routing options, the options selected from a group of options based on the calling line information and the retrieved subscriber profile.

8. (Original) The method of claim 7 further comprising:

based on the retrieved subscriber profile, identifying a call group with which the
calling line information is associated;

providing the menu of call routing options customized for the calling party based
on the call group.

9. (Currently amended) [[A]] An Advanced Information Network (AIN)

telecommunication system comprising:

a network element configured for processing a call between a calling party and a called
party; and

computer readable program code stored at the network element and including
first code to obtain a subscriber profile from a database of a Service
Control Point (SCP) of the AIN telecommunication system for the
called party;

second code to determine information about the calling party based on
information provided for the call by the SCP; and

third code to format a menu of call routing options customized for the
calling party based on the subscriber profile and the information
about the calling party.

10. (Currently amended) A method for routing calls in a telecommunication system, the
method comprising:

receiving a call from a calling party for a called party;

detecting a terminating number associated with the call;

based on the terminating number, determining if the called party is a subscriber to
a call routing service;

based on the terminating number, retrieving a stored subscriber profile;

based on the stored subscriber profile, playing a subscriber-defined announcement
of call routing options;

detecting a menu selection of the calling party; and

based on the menu selection and the subscriber profile, routing the call.

11. (Cancelled)

12. (Currently amended) The method of claim ~~11~~ 10 further comprising:

if the called party is a subscriber, routing the received call to designated network equipment for processing.

13. (Original) The method of claim 12 wherein routing the received call comprises routing the received call to one of a service node and an intelligent peripheral of the telecommunication system.

14. (Original) The method of claim 12 wherein playing a subscriber-defined announcement comprises:

playing a standard announcement selected by the subscriber.

15. (Original) The method of claim 12 wherein playing a subscriber-defined announcement comprises:

playing a recorded announcement recorded by the subscriber.

16. (Original) The method of claim 12 wherein playing a subscriber-defined announcement comprises:

retrieving subscriber-defined message data; and
converting the message data to an audible announcement.

17. (Original) The method of claim 12 wherein detecting a menu selection of the calling party comprises:

detecting dual tone, multiple frequency input of the calling party.

18. (Original) The method of claim 12 wherein detecting a menu selection of the calling party comprises:

detecting personal identification number data entered by the calling party;
comparing the personal identification number data with subscriber-stored data of the subscriber profile;
routing the call according to the subscriber profile.

19. (Currently amended) ~~[[A]]~~ An Advanced Information Network (AIN) telecommunication system comprising:

a ~~network element~~ compact service node configured to process a call from a calling party, the call having an associated terminating number;
first code operative in conjunction with the compact service node to retrieve from a database of a Service Control Point (SCP) of the AIN telecommunication system a subscriber profile of the calling party based on the terminating number;
second code operative in conjunction with the compact service node to play a subscriber-defined announcement of call routing options;
third code operative in conjunction with the compact service node to detect a menu selection of the calling party; and
fourth code operative in conjunction with the compact service node to communicate call routing information from the ~~network element~~ compact service node to call routing equipment of the AIN telecommunication system.

20. (Currently amended) The telecommunication system of claim 19 wherein the ~~network element~~ compact service node comprises a service node.

21. (Currently amended) The telecommunication system of claim 19 wherein the ~~network element~~ compact service node comprises an intelligent peripheral.

22. (Currently amended) The telecommunication system of claim 19 further comprising:
an originating Service Switching Point; and
a terminating Signal Switching Point in data communication with the network
element.

23. (Currently amended) The telecommunication system of claim 21 further comprising
a Service Control Point in data communication with the originating Service Switching Point, the
terminating Signal Switching Point and the ~~network element~~ compact service node to
communicate call routing information in the telecommunication system.

24. (Original) A call routing method in an Advanced Intelligent Network (AIN), the
method including:

at an originating switch, receiving a call from a calling communication station for
a directory number (DN);
communicating data about the call to a Service Control Point (SCP) of the AIN;
retrieving subscriber routing information associated with the DN;
in response to the subscriber routing information, initiating an interactive
communication between an Intelligent Peripheral (IP) of the AIN and the
calling communication station;
communicating information about call routing data received from the calling
communication station from the IP to the SCP; and
in response to the information, routing the call from the originating switch to a
terminating switch.

25. (Original) The call routing method of claim 24 further comprising:
communicating between the SCP and the IP according to GR1129 protocol.

26. (Original) The call routing method of claim 25 further comprising:
encrypting at least one of data and instructions in a message of the GR1129
protocol; and

decrypting the message to extract the at least one of data and instructions.

27. (Original) The call routing method of claim 26 further comprising:
- at the SCP, encrypting information about call routing options in a first message;
 - at the IP, decrypting the first message to extract the information about the call routing options; and
 - using the information about the call routing options, communicating call routing option data from the IP to the calling communication station.

28. (Original) The call routing method of claim 26 further comprising:
- at the IP, encrypting the information about the call routing data in a second message; and
 - at the SCP, decrypting the second message to extract the information about the call routing data.

29. (Original) A call routing method in an Advanced Intelligent Network (AIN), the method including:
- receiving a call from a calling party for a called party at an originating switch;
 - in response to a trigger on the call, sending data about the call from the originating switch to Service Control Point (SCP) of the AIN;
 - at the SCP, retrieving call routing option data associated with the called party;
 - in response to the call routing option data, activating an Intelligent Peripheral (IP) of the AIN to provide one or more menu options and receive one or more menu choices from the calling party;
 - providing information about the one or more menu choices from the IP to the SCP; and
 - in response to the information, routing the call from the originating switch to a terminating switch of the AIN.

30. (Original) The call routing method of claim 29 wherein activating the IP to provide one or more menu options comprises at least one of:

- playing an audible announcement to the calling party from the IP;
- converting text to speech data to an audible announcement from the IP; and
- playing a called party pre-recorded announcement to the calling party from the IP.

31. (Original) The call routing method of claim 29 wherein activating the IP to receive one or more menu choices comprises at least one of:

- detecting a keypad entry menu selection at the IP; and
- detecting audible speech of the calling party at the IP.

32. (Original) The call routing method of claim 29 further comprising:

- communicating between the IP and the SCP in accordance with GR1129 protocol.

33. (Original) The call routing method of claim 32 further comprising:

- at the SCP, encrypting a plurality of command instructions for the IP in a GR1129 message; and
- at the IP, decrypting the plurality of command instructions from the GR1129 message.

34. (Original) The call routing method of claim 32 wherein encrypting the plurality of command instructions comprises:

- formatting the GR1129 message with code data indicative of the plurality of command messages for retrieval at the IP.

35. (Original) The call routing method of claim 34 wherein decrypting the plurality of command instructions comprises:

- receiving the code data; and
- using the code data to retrieve data and instructions from a memory of the IP.

36. (Original) The call routing method of claim 29 further comprising:
storing call routing information for the call at the SCP.
37. (Original) An Advanced Intelligent Network comprising:
an originating switch configured to communicate information about a received call intended for a dialed Directory Number (DN);
a service node/intelligent peripheral (SN/IP) configured to provide call routing menu options to the originating switch and collect call routing menu choices from the originating switch;
a Service Control Point (SCP) in data communication with the originating switch and the SN/IP according to GR1129 protocol, the SCP configured to receive the information about the received call, retrieve stored subscriber routing information associated with the DN in response to the information and to use the SN/IP as a call routing information resource, the SCP further configured to route the call to a terminating switch in accordance with the subscriber routing information and information from the SN/IP about one or more call menu routing choices.
38. (Original) The Advanced Intelligent Network of claim 37 wherein the SCP comprises data storage means for storing the subscriber routing information.
39. (Original) The Advanced Intelligent Network of claim 37 wherein the SCP is further configured to communicate information about the call routing menu options to the SN/IP based on the subscriber routing information.
40. (Original) A data communication method for an Advanced Intelligent Network, the method comprising:
receiving a GR1129 message containing a selected code;
using the selected code, retrieving at least one of data and program instructions from storage; and

executing using the retrieved at least one of data and program instructions.

41. (Original) An Advanced Intelligent Network comprising:

- a first network element;
- a second network element in communication with the first network element using GR1129 protocol; and
- a program code stored at the second network element and selectable in response to a code included in a GR1129 message.

42. (Original) The Advanced Intelligent Network of claim 41 wherein the second network element comprises:

- a memory; and
- a processor configured to execute instructions stored in the memory including the program code upon receipt of the code.

43. (Original) The Advanced Intelligent Network of claim 42 wherein the memory comprises:

- a table indexed by the code.

44-46. (Cancelled)

47. (Original) A method for establishing call routing information from a subscriber to a call routing service, the method comprising:

- providing a World Wide Web display including data entry slots configured to receive verbal call destination indicators and corresponding telephone numbers;
- receiving a data transmission containing data related to the verbal call designation indicators and the corresponding telephone numbers; and
- storing the data for subsequent access.

48. (Original) The method of claim 47 wherein receiving the data transmission comprises receiving one or more TCP/IP packets from the subscriber over the Internet.

49. (Original) The method of claim 47 wherein receiving the data transmission comprises receiving a subscription number associated with the subscriber.

50. (Original) A user interface for updating subscriber specific call routing menu choices, the user interface comprising:

- one or more call termination option fields;
- one or more telephone number fields, each telephone number field corresponding to a call destination option; and
- a select button.

51. (Original) The user interface of claim 50 further comprising:
clickable call termination buttons.

52. (Original) The user interface of claim 50 further comprising:
clickable call destination buttons; and
clickable called party buttons.

53. (Currently amended) A call routing method in a telecommunication network, the method comprising:

- receiving a call from a caller, the call including a subscriber-identifying directory number subscriber identifier;
- identifying a service subscriber associated with the subscriber-identifying directory number subscriber identifier;
- retrieving a subscriber profile of the service subscriber including a list of call routing options and a subscriber-specific message for playback to the caller;
- playing the subscriber-specific message to the caller;

receiving a caller routing indication from the caller; and
routing the call to a terminating Directory Number (DN) associated with the call routing indication.

54. (Original) The method of claim 53 wherein retrieving the subscriber profile comprises:

retrieving a subscriber-specified list of terminating DN options;
retrieving a list of verbal descriptions, each verbal description of the list being associated with a terminating DN option of the list of terminating DN options; and
assigning a menu choice indicator to each terminating DN option and verbal description combination.

55. (Original) The method of claim 53 wherein receiving the call comprises:
detecting a toll free DN associated with the service subscriber.

56. (Original) The method of claim 54 wherein routing the call includes routing the call from the first telecommunication network to the second telecommunication network.

57. (Original) The method of claim 56 wherein the first telecommunication network comprises a landline telephone system and the second telecommunication network comprises a radiotelephone network.

58. (Currently amended) A call routing method comprising:
receiving a call from a caller for a service subscriber;
routing the call to a directory number (DN) associated with the service subscriber;
if the call is not answered at the DN, offering the caller additional call routing options; and
upon selection of an additional call routing option by the caller, charging the caller a fee for routing the call in accordance with the selected option; and

routing the call in accordance with the selected option ~~options~~.

59. (Original) The method of claim 58 further comprising:
if the call is not answered at the DN,
retrieving a subscriber profile, and
playing a voice mail option message based on the subscriber profile.
60. (Original) The method of claim 59 further comprising:
playing a message offering the caller additional call routing options in accordance
with the subscriber profile; and
receiving caller input,
routing the call according to the caller input and the subscriber profile.
61. (Original) The method of claim 60 further comprising:
offering a sequential contact option and a simultaneous contact option;
receiving a caller input;
if the simultaneous contact option is selected, routing the call simultaneously to a
plurality of directory numbers as specified by the subscriber profile;
if the sequential contact option is selected, offering an option to specify a contact
sequence;
receiving a contact sequence from the caller;
routing the call sequentially in accordance with the received contact sequence and
the subscriber profile.
62. (Original) A telecommunication system comprising:
call processing equipment;
a platform in communication with the call processing equipment, the platform
storing data defining a subscriber profile for menu-based call routing, the
data comprising:
a landline directory number;

- a voice mailbox identifier;
- a radiotelephone directory number;
- a facsimile directory number;
- a preferred group of directory numbers for simultaneous ringing during menu-based call routing; and
- a preferred sequence of directory numbers for sequential ringing during menu-based call routing.

63. (Original) A telecommunication system comprising:

- a Service Control Point (SCP) which routes calls in the telecommunication system, the SCP including
 - a SCP database storing call routing information and subscriber profile information, and
 - service logic to control call routing in the telecommunication system; and
- a service node in communication with the SCP and responsive to command data received from the service logic for interaction during a call with a caller to provide to the caller a menu of call routing options based on the subscriber profile, receive a call routing selection from the caller and return call routing selection data to the SCP for routing of the call by the SCP based on the call routing selection.

64. (Original) The telecommunication system of claim 63 further comprising:

- an Internet access portal in data communication with the SCP database for remote access and updating of the subscriber profile by a subscriber.

65. (Original) The telecommunication system of claim 63 wherein the SCP and the service node are configured for communication according GR1129 protocol.

66. (Original) A telecommunication system comprising:

- a Service Control Point (SCP) including

a SCP database storing call routing information, and
service logic to control call routing in the telecommunication system and
identify a service subscriber; and
a service node (SN) in communication with the SCP, the SN including
a SN database to store a subscriber profile, and
SN service logic responsive to a command issued from the SCP upon
identification of a service subscriber for interaction during a call
with a caller to provide to the caller a menu of call routing options
based on the subscriber profile, receive a call routing selection
from the caller, the service logic being configured to route the call
based on the call routing selection.

67. (Original) The telecommunication system of claim 66 further comprising:
an Internet access portal in data communication with the SN database for remote
access and updating of the subscriber profile by a service subscriber.